

COMMUNICATION ADAPTER

BACKGROUND

Field:

[0001] The subject matter disclosed herein relates to power management systems. In particular, the subject matter disclosed herein relates to power management systems in communication or computing devices.

Information:

- [0002] Environmental regulations have imposed restrictions on the rate of power consumption of processing platforms such as personal computer systems. Portability and form factor requirements have also motivated designs of processing platforms with reduced power consumption. Such a processing platform may transition to one or more power states as defined in the Advanced Configuration and Power Interface (ACPI) upon detecting an event or condition. For example, a processing platform may transition to a lower power state and resume to a full power condition upon detection of an event.
- [0003] In addition to a host processing system, a processing platform may include one or more peripheral devices. Such peripheral devices may include, for example, network adapters and other input/output devices. Peripheral devices typically consume power and contribute to the overall power consumption of the processing platform.

BRIEF DESCRIPTION OF THE FIGURES

[0004] Non-limiting and non-exhaustive embodiments of the present invention will be described with reference to the following figures, wherein like reference numerals refer to like parts throughout the various figures unless otherwise specified.

[0005] Figure 1 shows a processing platform according to an embodiment of the present invention.

[0006] Figure 2 shows a flow diagram illustrating a process of placing a communication adapter in a reduced power state according to an embodiment of the processing platform shown in Figure 1.

DETAILED DESCRIPTION

[0007] Reference throughout this specification to “one embodiment” or “an embodiment” means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment of the present invention. Thus, the appearances of the phrase “in one embodiment” or “an embodiment” in various places throughout this specification are not necessarily all referring to the same embodiment. Furthermore, the particular features, structures, or characteristics may be combined in one or more embodiments.

[0008] “Machine-readable” instructions as referred to herein relates to expressions which may be understood by one or more machines for performing one or more logical operations. For example, machine-readable instructions may comprise instructions which are interpretable by a processor compiler for executing one or more operations one or more data objects. However, this is merely an example of machine-readable instructions and embodiments of the present invention are not limited in this respect.

[0009] “Storage medium” as referred to herein relates to media capable of maintaining expressions which are perceivable by one or more machines. For example, a storage medium may comprise one or more storage devices for storing machine-readable instructions. However, this is merely an example of a storage medium and embodiments of the present invention are not limited in this respect.

[0010] “Logic” as referred to herein relates to structure for performing one or more logical operations. For example, logic may comprise circuitry which provides one or more output signals based upon one or more input signals. Such circuitry may comprise a finite state machine which receives a digital input and provides a digital output, or circuitry which provides one or more analog output signals in response to

one or more analog input signals. Also, logic may comprise processing circuitry in combination with machine-executable instructions stored in a memory. However, these are merely examples of structures which may provide logic and embodiments of the present invention are not limited in these respects.

[0011] A “processing system” as discussed herein relates to a combination of hardware and software resources for accomplishing computational tasks. However, embodiments of the present invention are not limited in this respect. A “host processing system” relates to a processing system which may be adapted to communicate with a “peripheral device.” For example, a peripheral device may provide inputs to or receive outputs from an application process hosted on the host processing system. However, embodiments of the present invention are not limited in this respect.

[0012] A “data bus” as referred to herein relates to circuitry for transmitting data between devices. For example, a data bus may transmit data between a host processing system and a peripheral device. However, this is merely an example and embodiments of the present invention are not limited in this respect. A “bus transaction” as referred to herein relates to an interaction between devices coupled in a bus structure wherein one device transmits data addressed to the other device through the bus structure.

[0013] A “device driver” as referred to herein relates to a process hosted on a processing system to facilitate communication between a peripheral device and one or more other processes hosted on the processing system. For example, a device driver may define one or more data items common with other processes on the processing system to enable data to be transmitted to or received from a peripheral

device. However, this is merely an example of a device driver and embodiments of the present invention are not limited in this respect.

[0014] A “power state” as referred to herein relates to a state in which a processing platform, or subsystem of a processing platform, may consume power. For example, a “reduced power state” may define a state at which power consumption of a device may be reduced from power consumption at a “full power state.” From a reduced power state, the device may “resume” (or be restored) to a full power in response to a condition or event. However, these are merely examples of a power state, full power state, reduced power state and a resume, and embodiments of the present invention are not limited in this respect.

[0015] A “power management system” as referred to herein relates to a combination of hardware and software resources in a processing platform to place one or more subsystems of the processing platform in a reduced power state, and cause the one or more subsystems to resume to a full power state in response to a condition or event. However, this is merely an example of a power management system and embodiments of the present invention are not limited in this respect.

[0016] A “sleep message” as referred to herein relates to a message provided to a subsystem of a processing platform to place the subsystem in a reduced power state. For example, a device driver may place an associated device in a reduced power state in response to a sleep state. However, this is merely an example of a sleep message and embodiments of the present invention are not limited in this respect.

[0017] A “transmission medium” as referred to herein relates to any media suitable for transmitting data. A transmission medium may include any one of several mediums including, for example transmission cabling, optical transmission medium or

wireless transmission media. However, these are merely examples of transmission media and embodiments of the present invention are not limited in this respect.

[0018] A “communication adapter” as referred to herein relates to a device which may be coupled to a transmission medium to transmit data to or receive data from other devices coupled to the transmission medium. For example, a communication adapter may comprise a network adapter adapted to transmit data to or receive data from devices coupled to a network such as a local area network. Such a network adapter may be communicate with the other devices according to any one of several data communication formats such as, for example, communication formats according any of the IEEE 802.3, asynchronous transfer mode (ATM), synchronous optical network (SONET) or synchronous digital hierarchy (SDH) standards. In alternative embodiments, a communication adapter may comprise any one of other I/O devices such as, for example, an adapter to a data storage system. However, these are merely examples of a communication adapter and embodiments of the present invention are not limited in these respects.

[0019] A “clock signal” as referred to herein relates to a periodic signal generated to synchronize or control one or more devices. For example, a clock signal may be generated at a particular “clock speed” or “clock frequency” to control the operation of one or more circuits of a device. However, these are merely examples of a clock signal and a clock speed, and embodiments of the present invention are not limited in this respect.

[0020] A “communication protocol” as referred to herein relates to a format or process in which information may be transmitted in a transmission medium between or among devices. A communication protocol may be characterized by a data rate, modulation or encoding format or data encapsulation format. Also, a

communication protocol may be characterized by transmitting data between devices in a full-duplex or half-duplex fashion. Also, a communication protocol may, but not necessarily, be applicable to transmitting data in a particular transmission medium. Other communication protocols may define communication formats which are independent of particular transmission media. However, these are merely examples of a communication protocol and embodiments of the present invention are not limited in these respects.

[0021] An “auto-select” mode as referred to herein relates to a state of a communication adapter coupled to a first node on a transmission medium while processing data received from the transmission medium. For example, while in an auto-select mode, the communication adapter may process information received from a second node coupled to the transmission medium to determine a communication protocol available for communicating with the second node. However, this is merely an example of an auto-select mode and embodiments of the present invention are not limited in this respect.

[0022] Briefly, an embodiment of the present invention relates to a system and method of controlling a communication adapter in response to a sleep message generated by a power management system. In response to a receiving a sleep message, the speed of a clock signal controlling the communication adapter may be reduced to place the communication adapter in a reduced power state. However, this is merely an example embodiment and embodiments of the present invention are not limited in this respect.

[0023] Figure 1 shows a processing platform 10 according to an embodiment of the present invention. A central processing unit (CPU) 12 and system memory 14 are coupled to a memory bridge 18 to provide a host processing system. A basic

input/output system (BIOS) 16 may load firmware instructions to the system memory 14 to be executed by the CPU 12 in response to a reset event. The firmware instructions may comprise routines to initialize the processing system by, for example, loading an operating system and device drivers to the system memory 14 from a non-volatile memory device (not shown).

[0024] A data bus 24 is coupled to the memory bridge 18 through an I/O bridge 20 to couple one or more peripheral devices to the memory bridge 18. Such peripheral devices may comprise a communication adapter 26 to transmit data to or received data from a transmission medium 28. In the illustrated embodiment, the data bus 24 may comprise a data bus structure formed according to the Peripheral Components Interconnect (PCI) data bus as provided in the PCI Local Bus Specification Rev. 2.2, December 18, 1998 (*hereinafter* the “PCI Local Bus Specification”). Also, a switch 30 may be coupled to the I/O bridge at an upstream port to enable point-to-point communication between devices (not shown) coupled to downstream ports independently of the I/O bridge 20. However, these are merely examples of how a peripheral device may be coupled to a host processing system and embodiments of the present invention are not limited in this respect.

[0025] The processing platform 10 may comprise a power management system comprising one or processes hosted on the CPU 12 and system memory 14 to communicate with one or more subsystems of the processing platform 10. For example, the power management system may place the subsystems in a reduced power state by providing sleep messages to the subsystems in response to detecting one or more events or conditions. The power management system may cause the subsystems to subsequently resume to a full power state in response to other events. For example, the power management system may place the processing platform 10

in a reduced power state in response to detecting a user input from a mechanical interface (not shown) or detecting an absence of activity at the CPU 12 (e.g., absence of interrupt signals from I/O devices). From the reduced power state, the power management system may transition one or more subsystems of the processing platform 10 to a full power state in response to, for example, a user input from the mechanical interface or detection of an interrupt to the CPU 12. The power management system may be formed according to the Advanced Configuration and Power Interface (ACPI) as illustrated in the ACPI Specification, Rev. 1.0b, February 2, 1999 (*hereinafter* the “ACPI Specification”). However, these are merely examples of a power management system used in conjunction with a processing platform and embodiments of the present invention are not limited in these respects.

[0026] The communication adapter 26 may comprise an interface with the data bus 24 enabling the communication adapter 26 to communicate with processes hosted on processing system using read or write bus transactions. The CPU 12 and system memory 14 may host a device driver that initiates bus transactions to communicate with the communication adapter 26. For example, the device driver may initiate a write transaction on the data bus 24 addressed to the communication adapter 26 to provide data in registers defined at an interface with the communication adapter 26. Additionally, the communication adapter 26 may initiate a write transaction on the data bus 24 to provide data to data buffers in the system memory 14. However, these are merely examples of how a peripheral device may communicate with processes hosted on a processing system through bus transactions and embodiments of the present invention are not limited in these respects.

[0027] The communication adapter 26 may comprise a network adapter which is coupled to a communication network such as a local area network (LAN). Such a network adapter may communicate with devices coupled to the communication network using any one of several communication protocols including, for example, communication protocols provided in IEEE 802.3, IEEE 802.3u, IEEE 802.11ab, ATM and SONET/SDH compliant systems. Alternatively, the communication adapter may comprise other types of input/output devices such as, for example, a small computer system interface (SCSI) device, Fibre-channel, ATA serial bus, Universal Serial Bus, IEEE 1394 and the like. However, these are merely examples of a communication adapter which may transmit data to or receive data from a transmission medium, and embodiments of the present invention are not limited in this respect.

[0028] The transmission medium 28 may comprise any medium capable of transmitting data. The transmission medium 28 may comprise category 5, coaxial or optical cabling, or wireless transmission media. The transmission medium 28 may also comprise any combination of the aforementioned cabling or wireless transmission media. However, these are merely examples of media which may be suitable for the transmission of data and embodiments of the present invention are not limited in these respects.

[0029] According to an embodiment, the communication adapter 26 may be controlled to transmit data to, or receive data from, the transmission medium 28 according to any one of a plurality of communication protocols. For example, in an embodiment in which the communication adapter 26 comprises a network adapter to communicate with other devices according to communication protocols provided in IEEE 802.3, the communication adapter may comprise logic to perform

autonegotiation to select a protocol for communication with the transmission medium from among protocols at different data rates such as 10Mbps (e.g., 10Base-T), 100Mbps (e.g., 100Base-T) and 1000Mbps (e.g., 1000Base-T).

[0030] Prior to completing autonegotiation with other devices to select a protocol, the communication adapter 26 may process data received from the transmission medium 28 while in an auto-select mode to determine a protocol for communicating with one or more nodes coupled to the transmission medium 28. In a model 82559ER Fast Ethernet Controller sold by Intel Corporation, for example, a physical unit auto-select function may determine an operational speed of a transmission medium based upon the receipt of link integrity pulses. If no Fast Link Pulses are detected and Normal Link Pulses are detected, the physical unit defaults to 10MBps operation. If the physical unit detects a line speed change (e.g., detects Fast Link Pulses), it may dynamically change its transmit and receive clock frequencies to match the change in line speed. However, this is merely an example of how a communication adapter may select a communication protocol to transmit data to or receive data from a transmission medium, and embodiments of the present invention are not limited in this respect.

[0031] In the presently illustrated embodiment, the communication adapter 26 may comprise circuitry that is synchronized by a periodic clock signal having a clock speed or clock frequency (the terms “clock speed” and “clock frequency” are *hereinafter* used interchangeably). The clock signal may be internally generated by the communication adapter 26 using techniques know to those of ordinary skill in the art of communication circuit design. However, this is merely an example of how a clock signal may be generated for the purpose of synchronizing circuitry in a

communication adapter and embodiments of the present invention are not limited in this respect.

[0032] To operate at different protocols or data rates, circuitry of the communication adapter 26 may be synchronized to operate at different speeds as controlled by the aforementioned clock signal. For example, the communication adapter 26 may comprise a media access controller (MAC) circuit (coupled to the data bus 24) and a physical communication circuit (phy) (coupled to the transmission medium 28) which are each controlled by one or more clock signals. In the previous example, where the communication adapter 26 may be adapted to communicate at either a 10Mbps, 100Mbps or 1000Mbps data rates, such a clock signal may be generated at a different corresponding clock speed for each data rate. For operation at 10Mbps, for example, a serial clock signal may be generated at 2.5 MHz. For operation at 100Mbps, for example, a serial clock signal may be generated at 25 MHz. For operation at 1000Mbps, for example, the serial clock signal may be generated at 250 MHz. Accordingly, such a serial clock signal may be generated at a highest clock speed to control the communication adapter 26 to communicate at the 1000Mbps data rate and generated at the lowest clock speed to control the communication adapter 26 to communicate at the 10Mbps data rate. However, these are merely examples of how a clock signal may be generated at different clock speeds to control a communication adapter to communicate at different data rates or communication protocols, and embodiments of the present invention are not limited in these respects.

[0033] In the illustrated embodiment, the CPU 12 and system memory 14 may host application programs and an operating system to manage processing system resources enabling the application programs. The operating system may comprise

encoded modules from any one of several commercially available operating systems such as, for example, versions of Windows™ sold by Microsoft Corporation, VxWorks™ or pSOS™ sold by WindRiver, Inc., Solaris™ sold by Sun Microsystems or Linux. However, these are merely examples of operating systems which may be hosted on a processing system, and embodiments of the present invention are not limited in this respect.

[0034] In addition to the operating system and application programs, the CPU 12 and system memory 14 may host one or more device drivers to facilitate communication between peripheral devices and other processes hosted on the CPU 12 and system memory 14. In particular, the CPU 12 and system memory 14 may host one or more device drivers associated with the communication adapter 26 to facilitate the transmission of data between the communication adapter 26 and the operating system. For example, such a device driver may define buffer locations in the system memory which are shared by an associated device and the operating system. However, these are merely examples of device drivers and embodiments of the present invention are not limited in this respect.

[0035] In some embodiments, the driver may be loaded to the system memory 14 from a non-volatile memory device (e.g., flash memory) in the BIOS 16 in response to a reset event. BIOS routines may then load the operating system to the system memory 14 from an external memory device (e.g., a hard disk drive, not shown) and initialize communication between the operating system and the device driver. In other embodiments, the device driver may be included in one or more modules of the operating system. In other embodiments, device drivers may be layered such that a first portion of device driver (e.g., lower layer) is loaded to the system memory 14 while a second portion of the devices driver is included in one or more

modules of the operating system. In this example, the first and second portions may define common data objects at an interface between the first and second portions. However, these are merely examples of a device driver and embodiments of the present invention are not limited in these respects.

[0036] According to an embodiment, one or more subsystems of the processing platform 10 may be controlled to be in one of a plurality of power states including a full power state, an off power state, and other intermediate power states. Each intermediate power state may be associated with a reduced rate of power consumption and latency for returning to the full power state in response to a resume procedure. For example, the processing platform 10 may be controllable to be in any of power states S0, S1, S2, S3, S4 or S5 according to the ACPI specification at section 2.4. However, this is merely an example of a power management system which defines a plurality of power states for a processing platform and embodiments of the present invention are not limited in this respect.

[0037] According to an embodiment, in response to placing the processing platform 10 in a reduced power state, the power management system may place the communication adapter 26 in a reduced power state by, for example, transmitting a sleep message to the device driver of the communication adapter 26. In one embodiment, the communication adapter 26 may be controllable to be in any of power states D0, D1, D2 or D3 as defined in the ACPI Specification at section 2.3. In response to the sleep message, the device driver may transmit one or more messages to the communication adapter 26 through the data bus 24. In one example, the device driver may initiate a bus transaction to write data to a register of the communication adapter 26 to place the communication adapter in a reduced power state. In response, the communication adapter 26 may initiate one or more

subsequent bus transactions to save local data in a location of the system memory 14 before transitioning to the reduced power state. Upon resuming to a full power state, the communication adapter 26 may retrieve the local data from the system memory 14. However, this is merely an example of how a communication adapter may transition to a reduced power state and resume to a full power state, and embodiments of the present invention are not limited in this respect.

[0038] In one embodiment, the communication adapter 26 comprises an interface with the data bus 24 to receive messages from the device driver to specify a communication protocol, or control the clock speed of a clock signal controlling one or more circuits of the communication adapter 26. Such an interface may be accessible through a read or write transaction on the data bus 24 addressed to the communication adapter. In response to receiving a sleep message from the power management system, the device driver may place the communication adapter 26 in a reduced power state by writing to a register in this interface to either specify a lower clock speed to control the one or more circuits of the communication adapter 16 or specify a communication protocol using less power (e.g., a communication protocol that causes the communication adapter 26 to use less power). However, this is merely an example of how a device driver may place a communication adapter in a reduced power state in response to a sleep message and embodiments of the present invention are not limited in this respect.

[0039] Figure 2 shows a flow diagram illustrating a process 100 of placing a communication adapter in a reduced power state according to an embodiment of the processing platform shown in Figure 1. In the illustrated embodiment, the process 100 may be controlled by a device driver hosted on the CPU 12 and system memory 14. However, this is merely an example implementation of a process to

place a communication adapter in a reduced power state and embodiments of the present invention are not limited in this respect

[0040] At block 102, the device driver may receive a sleep message from the power management system indicating that the processing platform 10 is transitioning to a reduced power state (e.g., from S0 to S1, S2, S3 or S4 as defined in the ACPI specification). This signal may be provided by the power management system in a data item in the system memory 14 which is accessible by the device driver as part of a call to the device driver. However, this is merely an example of how a device driver may receive a sleep message indicating a transition to a lower power state and embodiments of the present invention are not limited in this respect.

[0041] Upon receipt of a sleep message at block 102, diamond 104 determines whether the communication adapter 26 is operating at a higher power state (e.g., a power state which consumes more power than while operating at the reduced power state). In the illustrated embodiment, diamond 104 determines whether the communication adapter is operating at state to support a communication protocol having a data rate exceeding a threshold data rate corresponding with the reduced power state. For example, the communication adapter 26 may comprise logic to communicate with other nodes coupled to the transmission medium 28 according to any of the 10Base-T, 100Base-T or 1000Base-T communication protocols defined in versions of the IEEE standard 802.3. As the communication adapter 26 may consume more power at the 100Base-T (at 100Mbps) or 1000Base-T (at 1000Mbps) protocols than at the 10Base-T protocol (at 10Mbps), diamond 104 may apply a threshold data rate at 10Mbps to determine whether the communication adapter 26 is operating at a state which consumes more power than the lowest power state.

[0042] In an alternative embodiment, block 104 may determine that a clock signal controlling circuitry of the communication adapter 26 has a clock speed above a threshold clock speed. In the illustrated embodiment, the threshold clock speed may be a clock speed for controlling the communication adapter to operate at a lowest data rate (e.g., 10Mbps at 10Base-T). This clock speed may be provided in a data item which is maintained by the communication adapter (e.g., through bus transactions on the data bus 24) and accessible by the device driver. In an embodiment in which the communication adapter 26 comprises a 82559ER Fast Ethernet controller sold by Intel Corporation, for example, a Management Data Interface (MDI) may provide status information and accept management information. Here, bits 11 through 14 in register 1 may indicate a current operation mode of the physical circuit. These bits may be examined upon transitioning to a reduced power state to determine whether the clock speed is set for operating at 10Mbps or 100Mbps. However, these are merely examples of how a device driver may determine whether an associated communication adapter is operating at a higher power state, and embodiments of the present invention are not limited in these respects.

[0043] If the communication adapter 26 is not operating the higher power state (e.g., to support a communication protocol having a data rate that does not exceed the threshold data rate) at diamond 104, block 108 may initiate a procedure to place the communication adapter in the lower power state. Such a procedure at block 108 may include, for example, writing data to the system memory 14 to preserve the local system state and removing power from one or more portions of the communication adapter 26. Otherwise, if diamond 104 determines that the communication is operating at a higher power state (e.g., to support a

communication protocol having a data rate exceeding the threshold data rate), block 106 causes the communication adapter 26 to operate at the lower power state by, for example, causing the speed of the clock signal to be lowered (e.g., a clock speed corresponding with the reduced power state) prior to the procedure initiated at block 108. Block 108 may then cause the communication adapter 26 to complete a transition to a reduced power state as discussed above. With the lowered clock speed, the communication adapter 26 may then consume less power than at the clock speed applied for operating at the protocol having the higher data rate.

[0044] Following a transition of the communication adapter 26 to the lower power state at block 108, the power management system may provide a resume signal to the device driver indicating that the processing platform 10 is resuming to a full power state. In response to the resume signal, the device driver may provide a signal to the communication adapter 26 to “awaken” the communication adapter from the reduced power state at block 110 by, for example, resetting the speed of the clock signal controlling circuitry of the communication adapter 26. The device driver may reset the speed or frequency of the clock signal by, for example, initiating subsequent a write transaction on the data bus 24 to the register in the interface of the communication adapter 26 specifying the clock speed. The reset clock signal may then maintain the communication adapter 26 in an autosensing mode to process data received from the transmission medium 28.

[0045] While there has been illustrated and described what are presently considered to be example embodiments of the present invention, it will be understood by those skilled in the art that various other modifications may be made, and equivalents may be substituted, without departing from the true scope of the invention. Additionally, many modifications may be made to adapt a particular situation to the

teachings of the present invention without departing from the central inventive concept described herein. Therefore, it is intended that the present invention not be limited to the particular embodiments disclosed, but that the invention include all embodiments falling within the scope of the appended claims.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222